

# ThermoSave®

Ceramic Thermal Insulating Coating

PIENNE SERVICES SRL

Distributore Ufficiale

VIA MARIA 230, 03029 Veroli (FR)

Email: [info.pienneservicesrl@gmail.com](mailto:info.pienneservicesrl@gmail.com)

P.IVA 02971050600



# PRIMER U-250

Waterborne Ecologic Primer

## Technical Data Sheet



# TOP COLOR PRIMER

## Technical Data Sheet

### DESCRIPTION

TOP COLOR PRIMER is a waterborne acrylic primer used as a base coat before applying TOP COLOR paint. It increases the adherence of the paint to the surface, decreases the absorption of the surface and stabilizes certain dust-prone surfaces. It is characterised by excellent flexibility, weatherability and resistance to light.

### RECOMMENDED FOR

It can be applied on indoor and outdoor surfaces made of screed, concrete, gypsum board, plaster, polishing plaster coat etc.

### TECHNICAL DATA

Appearance	White opaque fluid
Density at 20°C (g/cm <sup>3</sup> ) SR EN ISO 2811 - 1:2002	1.008 ± 0.007
Solid substance (%) SR EN ISO 3251:2003	min. 12
Brookfield Viscosity (cP) SR EN ISO 2555:2003	12,000 ± 1,000
pH	8 ÷ 9

# TOP COLOR PRIMER

## Technical Data Sheet

### APPLICATION TECHNOLOGY

Application is done by brush, roller or by airless spraying on dry, clean, dust-free surfaces.

**Estimated product consumption: 50 - 75 g/m<sup>2</sup>**

Do not apply at temperatures lower than 10°C.  
The paint can be applied only after the primer is dried.

**Estimated drying time: 1-2 hours**

The dried layer of primer is seamless and transparent.

### ENVIRONMENTAL, HEALTH & SAFETY INFORMATION

The product is waterborne, thus it doesn't need special measures of usage and protection.

Keep out of reach of children. Avoid contact with skin and eyes.

Don't dispose in sewage. Dispose the product and its package in safe places.

In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention.

If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

### PACKING, STORAGE, TRANSPORTATION

TOP COLOR is packed in sealed recipients of different sizes.

Store in cool, dry spaces, at temperatures of 5-30°C. Keep away from freezing or direct sunlight.

### WARRANTY

Warranted for 12 months from the production date, kept in recommended conditions.

**ThermoSave**<sup>®</sup>  
Ceramic Thermal Insulating Coating

**PIENNE SERVICES SRL**  
Distributore Ufficiale  
VIA MARIA 230, 03029 Veroli (FR)  
Email: [info.pienneservicesrl@gmail.com](mailto:info.pienneservicesrl@gmail.com)  
P.IVA 02971050600

Contact us



**Official Distributor - Italia:**

**PIENNE SERVICES SRL**

**SEDE: Via Maria 230, 03029 Veroli (FR)**

**Email: [info.pienneservicesrl@gmail.com](mailto:info.pienneservicesrl@gmail.com)**

**Mobile: +39 347 741 4755**